

PERFORMANCE GUIDE

Represents Typical Values Only

www.mactac.com

Revision: NDG 5/2021

PRODUCT CODE: 4-GL3B-05058

PRODUCT DESCRIPTION

3.2 mil gloss white vinyl for promotional use and other applications requiring a quality economical vinyl with a clear permanent acrylic adhesive.

APPLICATIONS

- Point of purchase
- Promotional graphics
- Short term signage
- Backlit
- Flat vehicle signage

FEATURES AND BENEFITS

• Ideal for promotional short term flat applications.

TECHNICAL DATA

Face Material 3.2 mil flexible vinyl

Color and Finish Gloss white

Adhesive 40 permanent acrylic emulsion

Liner 78# Clay coated Kraft

TYPICAL CHARACTERISTICS

Average Adhesion Values 15 min. 24 hr. (PSTC-1, 180° peel @ 12"/min., 73°F, Tested on SS 50 oz. 61 oz.

Minimum Application Temperature 50°F

Service Temperature Range -40°F to +180°F

Shelf Life (@ 73°F, 50% RH) 2 years Outdoor Durability 3 years

CHEMICAL RESISTANCE

Distilled Water (24 hr)

Detergent (24 hr)

No Effect

10% HC1 (10 min)

N/A

10% Ammonium Hydroxide (10 min)

Anti-Freeze (24 hr)

SAE 20 Motor Oil (24 hr)

Gasoline (1 hr)

No Effect

No Effect

No Effect

IMPORTANT NOTICE: The information given, and the recommendations made herein are based on our research and are believed to be accurate, but no guarantee of their accuracy or completeness is made. In every case, user shall determine before using any product in full scale production, or in any way, whether such product is suitable for user's intended use for their particular purpose under their own operating conditions. User assumes all risk and liability whatsoever in connection with their use of any product. The products discussed herein are sold without any warranty as to merchantability or fitness for a particular purpose, or any other warranty, express or implied. No representative of ours has any authority to waive or change the foregoing provisions, and no statement or recommendation not contained herein shall have any force of effect unless in an agreement signed by the officers of seller and manufacturer. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement, or recommendation to practice any invention covered by any patent without authority from the owner of the patent. The following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace or credit such quantity of the product proved to be defective at its discretion.

 $^{\text{\tiny{TM}}}$ Trademark of Morgan Adhesives Company.

® Registered Trademark of Morgan Adhesives Company.

